



TECHNICAL DATA SHEET

CI/SfB

76.7

3000 SERIES ROLLER BLIND

The 3000 Series Roller Blind is a system of roller blinds consisting of various sizes of roller tubes, mechanisms and bracketry to cover a wide variety of window sizes. The system is suitable for anything from attachment to doors, through to large areas of glazing.

The roller tubes are a strong and robust design extruded from aluminium to provide a rigid barrel which will resist deflection. The internal ribs strengthen the design to allow heavy weight screen-type and blackout fabrics to be used.

The mechanisms are manufactured from UV-resistant plastic to ensure a long life. The larger systems have a geared mechanism which can also be combined with an internal spring within the tube, which makes operation lightweight and easy. The side chains are manufactured from stainless steel and have an endless join to allow complete flexibility.

The blind hembar is normally concealed within the fabric to be unobtrusive. To give additional weight, a 22mm aluminium section is used which is a circular extrusion and finished in white (or any other RAL colour to order).

The larger systems can also be coupled with a full cassette system with an attractive rounded profile which fully contains the roller barrel, fabric and mechanism. Alternatively, a square fascia can be used to give the effect of a cassetted blind, or a concealing bulkhead whilst maintaining accessibility to the mechanics of the system.



For specifications and drawings please visit our website www.interlaceblinds.com

INTERLACE WARRANTY

InterLace 3000 Series Roller Blinds are covered against defective manufacturing for 12 months from the date of installation.

This warranty does not cover misuse, damage caused after installation, or vandalism. InterLace liability is limited to the replacement of defective products like for like only. InterLace is committed to a program of continuous product improvement.

Please be advised that specifications, performance, appearance, and dimensions of InterLace products are subject to change without notice. InterLace reserves the right to the final decision in the event of any warranty claim.

APPLICATION

- Vertical Windows
- High level windows
- Sloping windows with guide wires up to 15° from the vertical
- Large curtain walling
- Doors

CONTROL

- Manual crank handle
- Manual side chain (with chain-safe device)
- 240v Electric
- Control systems

HARDWARE

- Metal brackets and hembar with white powder coated finish
- Custom RAL finishes available

FABRIC

There is a wide range of fabrics available covering every situation:

- Solar shading
- Screening and privacy
- Dim-out and blackout

Call InterLace sales office on **0800 619 6999** to order samples or email your requirements to sales@interlaceblinds.com

FIXING

- Top fix
- Custom fixings available
- Face fix
- Side fix

SIZE

Barrel Size	32mm	40mm	45mm	45mm Geared
Max Width	2000mm	2500mm	3000mm	3500mm
Max Drop	4000mm	5000mm	6000mm	6000mm
Max Area (heavy fabric)	3m ²	7.5m ²	10.0m ²	10.0m ²
Max Area (light fabric)	6m ²	12.5m ²	15m ²	21m ²

SPECIAL OPTIONS

- Guide wires
- Fascia
- Banding (more than one blind operated by a single control)
- Aluminium hembar
- Sewn in hembar

3000 Series Roller Blinds can be customised in various ways. Please contact the sales office with your requirements.



INTERLACE
EST. 1976

InterLace® Blinds Ltd, Cambridge CB21 4XN | T: 0800 619 6999 | sales@interlaceblinds.com | www.interlaceblinds.com