

7000 SERIES FLYSCREEN



Operating and maintenance information

OPERATING INSTRUCTIONS

InterLace® 7000 Series Flyscreens are robust systems that are easy to operate and maintain.

The flyscreen is a spring loaded system which is drawn down by grasping the handles on the bottom bar and pulling downwards. While pulling the screen down, pull the bottom bar towards the room slightly and allow the bottom bar to run against the inside front of the side channels. When the screen reaches the bottom, compress the brush strip into the sill and tilt the top of the bottom bar forward until it clicks into the locks.

To retract, tilt the bottom bar back to release and allow the spring to retract the screen, guiding it with the handles. Do not allow to retract unrestrained as damage can occur. Please ensure that care is taken when using this product that fingers do not become trapped in the side guides or head cassette.



SUSTAINABILITY & RECYCLING

InterLace® works hard to reduce the environmental impact of its activities, and we regularly evaluate the lifecycle perspective of every product. This means that where possible, we reuse parts and recycle materials to reduce waste going to landfill. When disposing of your InterLace® product, please break the system down into the various materials and recycle through the correct channels. If you require any information regarding recycling, please contact InterLace® with details of the project and product and we will be glad to advise.



MAINTENANCE

InterLace® 7000 Series Flyscreens are designed to be maintenance free.

Mesh Care

Dust and dead flies should be regularly vacuumed from the mesh, taking care not to pierce the screen.

Lubrication

If operation becomes slow or stiff, a small amount of approved lubricant can ease the running of certain components as systems begin to age.

Note: Flyscreens are installed for the purpose of hygiene and must be drawn at all times when the window is open in order to comply with Food Safety Regulations. Please be aware that although designed for intensive use, screens are by nature delicate items and should be treated with respect. If at any point a mechanism becomes jammed or will not operate for any reason, contact InterLace® on **0800 619 6999** for advice. Do not ever force as this will result in further potential damage.

InterLace® state that an annual check should be carried out by a competent person, to ensure that the screens operate in the correct way, that any mesh is undamaged, and ensure that any parts requiring replacement are fitted as soon as possible. Spare parts of replaceable components and an approved lubricant are available from InterLace® on **0800 619 6999**.

InterLace® Warranty

InterLace® products are covered against defective manufacturing for 12 months from the date of installation.

This warranty does not cover misuse, builders damage after installation, or vandalism.

InterLace® liability is limited to the replacement of defective products like for like only.

InterLace® reserves the right to use discretion in the consideration of individual claims and the company's verdict is final.



INTERLACE
EST. 1976

InterLace® is committed to a continuing program of product improvement. Thus, please be advised that specifications, performance, appearance, and dimensions of InterLace® products are subject to change without notice.

InterLace® Blinds Ltd, Unit 6 The Grip Industrial Estate, Linton, Cambridge CB21 4XN
T: 0800 619 6999 | sales@interlaceblinds.com | www.interlaceblinds.com